

PRODUCT DATA SHEET

Cable Description

Cable Size	:	2X0.5 mm ² (Flat)
Standard Specification Applied To Cable	:	IEC 60227 - IEC 60228
Rated Voltage	:	300 / 300 Volt
Cable Description	:	Flexible Copper Conductor Insulated With Polyvinyl Chloride (CU / PVC)

Conductor

Standard Specification Applied To Conductor	:	IEC 60228
NO. Of Cores per Cable	:	2
Nominal Cross- Sectional Area Per core	:	0.5 mm ²
Nominal Number Of Strands Per core	:	16
Diameter Of Each Strand	:	0.20 mm
Material Of Core	:	Copper
Type	:	Class-5
Cross- Sectional Area Of Each Strand	:	0.0314 mm ²
Overall Diameter Of Conductor	:	0.8 mm
D.C. Resistance Of Conductor At 20°C Per Km (max.)	:	39.0 Ω/km

Insulation

Material Of Insulation	:	Polyvinyl Chloride
Colour Per Core	:	Black/Red
Nominal Thickness Of Insulation Per Core	:	0.80 mm
Min. Insulation Resistance Per Core Per Km Length Of Cable At 70°C	:	0.016 M ohm.Km
Test Voltage Between Cores And Earth (AC KV . Time min)	:	2000V for 5 min
Heat Resistance Test (Temperature °C . Time min)	:	150 °C for 1 hour

Over Sheath

Material Of Outer Jacket	:
Thickness Of Outer Jacket	:
Colour Of Outer Jacket	:

Cable Dimension (Nominal) :

Nominal External Cable Diameter	:	5.0X2.5 : 6.0X3.0 mm
--	---	----------------------