

## **PRODUCT DATA SHEET**

### **Cable Description**

<b>Cable Size</b>	:	4X4 mm <sup>2</sup>
<b>Standard Specification Applied To Cable</b>	:	IEC 60502 - IEC 60228
<b>Rated Voltage</b>	:	600 / 1000 Volt
<b>Cable Description</b>	:	Flexible Copper Conductor Insulated With Polyvinyl Chloride And Sheathed With Polyvinyl Chloride(CU / PVC / PVC)

### **Conductor**

<b>Standard Specification Applied To Conductor</b>	:	IEC 60228
<b>NO. Of Cores per Cable</b>	:	4
<b>Nominal Cross- Sectional Area Per core</b>	:	4 mm <sup>2</sup>
<b>Nominal Number Of Strands Per core</b>	:	56
<b>Diameter Of Each Strand</b>	:	0.30 mm
<b>Material Of Core</b>	:	Copper
<b>Type</b>	:	Class-5
<b>Cross- Sectional Area Of Each Strand</b>	:	0.07065 mm <sup>2</sup>
<b>Overall Diameter Of Conductor</b>	:	2.65 mm
<b>D.C. Resistance Of Conductor At 20°c Per Km (max.)</b>	:	4.95 Ω/km

### **Insulation**

<b>Material Of Insulation</b>	:	Polyvinyl Chloride
<b>Colour Per Core</b>	:	Red – Yellow – Blue – Black
<b>Nominal Thickness Of Insulation Per Core</b>	:	1.00 mm
<b>Min. Insulation Resistance Per Core Per Km Length Of Cable At 70°c</b>	:	0.0077 M ohm.Km
<b>Test Voltage Between Cores And Earth ( AC KV . Time min )</b>	:	3000V for 5 min
<b>Heat Resistance Test ( Temperature °c . Time min )</b>	:	150 °c for 1 hour